Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. **Product identifier**

Article No. (manufacturer/supplier): 4 07149 A0000
Trade name/designation: epple cast resin 07149
transparent
Component A
UFI: 1020-T0N7-C00S-1VH5

1.2. **Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses:
Casting resin for casting electronic and other components.

1.3. **Details of the supplier of the safety data sheet**

supplier (manufacturer/importer/downstream user/distributor)

E. Epple & Co. GmbH
Hertzstr. 8
71083 Herrenberg
Telephone: +49 7032 / 9771-17
Telefax: +49 7032 / 9771-60
www.epple-chemie.de

Department responsible for information:
laboratory
E-mail (competent person): labor@epple-chemie.de

1.4. **Emergency telephone number**
Information center against poisoning Bonn: +49 (0) 228 / 19 240 (Advice in German)

SECTION 2: Hazards identification

2.1. **Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.

2.2. **Label elements**

The product is classified and labelled according to EC directives or corresponding national laws.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Warning

Hazard statements

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P261	Avoid breathing vapours.
P280	Wear protective gloves.
P302 + P352	IF ON SKIN: Wash with plenty of water and soap.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/ container to an approved waste disposal plant.

Hazard components for labelling

bis-[4-(2,3-epoxipropoxi)phenyl]propane
Methyl toluene-4-sulfonate
1,6-hexanediol diglycidyl ether

Supplemental hazard information

EUH205	Contains epoxy constituents. May produce an allergic reaction.

2.3. **Other hazards**

No information available.

SECTION 3: Composition/information on ingredients

3.2. **Mixtures**

Description Epoxy resin based on bisphenol A

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. Index No.	REACH No. Designation classification: // Remark	weight-%
216-823-5 1675-54-3 603-073-00-2	01-2119456619-26 bis-[4-(2,3-epoxipropoxi)phenyl]propane Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Skin Sens. 1 H317 / Aquatic Chronic 2 H411 Specific concentration limit (SCL): Eye Irrit. 2 H319 >= 5 / Skin Irrit. 2 H315 >= 5	74,9 - 100
240-260-4 16096-31-4	01-2119463471-41 1,6-hexanediol diglycidyl ether Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Skin Sens. 1 H317 / Aquatic Chronic 3 H412	9,9 - 19,9
201-283-5 80-48-8	01-2120211468-59 Methyl toluene-4-sulfonate Acute Tox. 4 H302 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Skin Sens. 1 H317 / STOT SE 3 H335 Acute toxicity estimate (ATE): ATE (oral): 341 mg/kg bw	0,1 - 0,9

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. **Description of first aid measures**

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. **Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. **Extinguishing media**

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media
strong water jet

5.2. **Special hazards arising from the substance or mixture**
Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. **Advice for firefighters**
Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

SECTION 6: Accidental release measures

6.1. **Personal precautions, protective equipment and emergency procedures**
Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. **Environmental precautions**
Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. **Methods and material for containment and cleaning up**
Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. **Reference to other sections**
Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. **Precautions for safe handling**

Advices on safe handling

Avoid contact with skin, eyes and clothes. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Follow the legal protection and safety regulations.

7.2. **Conditions for safe storage, including any incompatibilities**

Requirements for storage rooms and vessels
Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage
Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions
Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. **Specific end use(s)**
Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**
Occupational exposure limit values

not applicable

DNEL:

bis-[4-(2,3-epoxipropoxi)phenyl]propane
Index No. 603-073-00-2 / EC No. 216-823-5 / CAS No. 1675-54-3
DNEL acute dermal, short-term (systemic), Workers: 8,3 mg/kg bw/day
DNEL long-term dermal (systemic), Workers: 8,3 mg/kg bw/day
DNEL acute inhalative (systemic), Workers: 12,3 mg/m³
DNEL long-term inhalative (systemic), Workers: 12,3 mg/m³

1,6-hexanediol diglycidyl ether
EC No. 240-260-4 / CAS No. 16096-31-4
DNEL acute dermal, short-term (local), Workers: 0,0226 mg/cm²

DNEL long-term dermal (systemic), Workers: 2,8 mg/kg bw/day
DNEL long-term inhalative (systemic), Workers: 0,44 mg/m³

PNEC:

bis-[4-(2,3-epoxipropoxi)phenyl]propane
Index No. 603-073-00-2 / EC No. 216-823-5 / CAS No. 1675-54-3
PNEC aquatic, freshwater: 6 µg/L
PNEC aquatic, marine water: 1 µg/L
PNEC aquatic, intermittent release: 0,013 mg/L
PNEC sediment, freshwater: 0,996 mg/kg dw
PNEC sediment, marine water: 0,1 mg/kg dw
PNEC, soil: 0,196 mg/kg dw
PNEC sewage treatment plant (STP): 10 mg/L

1,6-hexanediol diglycidyl ether
EC No. 240-260-4 / CAS No. 16096-31-4
PNEC aquatic, freshwater: 0,0115 mg/L
PNEC aquatic, marine water: 0,0011 mg/L
PNEC aquatic, intermittent release: 0,115 mg/L
PNEC sediment, freshwater: 0,283 mg/kg
PNEC sediment, marine water: 0,0283 mg/kg
PNEC, soil: 0,223 mg/kg
PNEC sewage treatment plant (STP): 1 mg/L

8.2. **Exposure controls**

Personal protection equipment

Respiratory protection
If the workplace limit values (AGW) are exceeded, a suitable breathing apparatus must be worn.Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.
Use filter / combination filter according to EN 14387.
Suitable respiratory protection apparatus: ABEK-P2

Hand protection
For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)
Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.
Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374
Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection
Wear eye glasses with side protection according to EN 166.

Protective measures
After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls
Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. **Information on basic physical and chemical properties**

Physical state:	**Liquid**
Appearance:	**Liquid**
Colour:	**translucent**
Odour:	**characteristic**
Odour threshold:	**not applicable**
Melting point/freezing point	**8 °C** Source: bis-[4-(2,3-epoxipropoxi)phenyl]propane
Initial boiling point and boiling range:	**not applicable**
Flammability:	**Combustible liquid.**
Lower and upper explosion limit:	

Lower explosion limit:	**not applicable**
Upper explosion limit:	**not applicable**
Flash point:	**149 °C**
Auto-ignition temperature:	**not applicable**
Decomposition temperature:	**not applicable**
pH at 20 °C:	**not relevant**
Kinematic viscosity (40°C):	**2400 mm²/s**
Viscosity at 20 °C:	**2 - 4 Pa*s**
Solubility(ies):	
Water solubility at 20 °C:	**insoluble**
Partition coefficient: n-octanol/water:	**see section 12**
Vapour pressure at 20 °C:	**not applicable**
Density and/or relative density:	
Density at 20 °C:	**1,25 g/cm³**
Relative vapour density:	**not applicable**
particle characteristics:	**not applicable**

9.2. **Other information**

Solvent separation test: **< 3 weight-% (ADR/RID)**

SECTION 10: Stability and reactivity

10.1. **Reactivity**
No information available.

10.2. **Chemical stability**
Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. **Possibility of hazardous reactions**
Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. **Conditions to avoid**
Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials**
not applicable

10.6. **Hazardous decomposition products**
Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. **Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute toxicity

bis-[4-(2,3-epoxipropoxi)phenyl]propane
oral, LD50, Rat: > 2000 mg/kg
dermal, LD50, Rat: > 2000 mg/kg
Method: OECD 402
dermal, LD50, Rabbit: > 2000 mg/kg

Methyl toluene-4-sulfonate
oral, LD50, Rat: 341 mg/kg

1,6-hexanediol diglycidyl ether
oral, LD50, Rat: 3741 mg/kg
dermal, LD50, Rat: > 2000 mg/kg
inhalative (vapours), LC50, Rat: > 0,035 mg/L (4 h)

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes skin irritation.

Causes serious eye irritation.

Methyl toluene-4-sulfonate
Skin, Rabbit (24 h): Evaluation strongly irritant.
eyes, Rabbit (24 h): Evaluation mild irritant.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Based on the properties of the epoxy constituents and considering toxicological data on similar preparations, this preparation may be a skin sensitiser and an irritant. It contains low molecular weight epoxy constituents which are irritating to eyes, mucous membrane and skin. Repeated skin contact may result in irritations and sensitizations, possibly due to a cross-over sensitization with other epoxy compounds. Skin contact with the preparation and exposure to spray mist and vapour should be avoided.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

11.2. **Information on other hazards**

Endocrine disrupting properties
No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Partition coefficient: n-octanol/water: Mixtures: Not applicable.Do not allow to enter into surface water or drains.

12.1. **Toxicity**

bis-[4-(2,3-epoxipropoxi)phenyl]propane
Fish toxicity, LC50: 1,3 mg/L (96 h)
Method: OECD 203
Daphnia toxicity, EC50: 2,1 mg/L (48 h)
Method: OECD 202

1,6-hexanediol diglycidyl ether
Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 30 mg/L (96 h)
Daphnia toxicity, EC50, Daphnia magna (Big water flea): 47 mg/L (48 h)

Long-term Ecotoxicity

Toxic to aquatic life with long lasting effects.

bis-[4-(2,3-epoxipropoxi)phenyl]propane
Daphnia toxicity, NOEC: 0,3 mg/L (21 d)
Method: OECD 211

12.2. **Persistence and degradability**

There are no data available on the preparation/mixture itself.

bis-[4-(2,3-epoxipropoxi)phenyl]propane
Biodegradation:: 5 % (28 d); Evaluation Not readily biodegradable (according to OECD criteria)
Method: OECD 301F
Biodegradation:: 6 - 12 % (28 d); Evaluation Not readily biodegradable (according to OECD criteria)
Method: OECD 301B

1,6-hexanediol diglycidyl ether
: 47 % (28 d); Evaluation Not readily biodegradable (according to OECD criteria)
Method: OECD 301D

12.3. **Bioaccumulative potential**

bis-[4-(2,3-epoxipropoxi)phenyl]propane
Partition coefficient: n-octanol/water: 2,64 - 3,78

1,6-hexanediol diglycidyl ether
Partition coefficient: n-octanol/water: 0,822
Method: OECD 107

Bioconcentration factor (BCF)

bis-[4-(2,3-epoxipropoxi)phenyl]propane
Bioconcentration factor (BCF): 3 - 31

1,6-hexanediol diglycidyl ether
Bioconcentration factor (BCF): < 100

12.4. **Mobility in soil**
Toxicological data are not available.

12.5. **Results of PBT and vPvB assessment**
The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. **Endocrine disrupting properties**
No information available.

12.7. **Other adverse effects**
No information available.

SECTION 13: Disposal considerations

13.1. **Waste treatment methods**

Appropriate disposal / Product
Recommendation
Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.Observe in addition any national regulations!

Switzerland: Disposal in accordance with the Ordinance on the Transport of Waste (VeVA) and the Ordinance on the Avoidance and Disposal of Waste (VVEA).

List of proposed waste codes/waste designations in accordance with EWC
080409* Waste adhesives and sealants containing organic solvents or other dangerous substances
*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package
Dispose of packaging and contaminated filters at a offical hazardous waste incinerator facility.
Recommendation:
Waste codes / waste designations according to EWC / AVV: 15 01 10*
Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1. **UN number or ID number**

UN 3082

14.2. **UN proper shipping name**

Land transport (ADR/RID):	Environmentally hazardous substance, liquid, n.o.s. (4,4'-methylene diphenyl diglycidyl ether)
Sea transport (IMDG):	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (4,4'-methylene diphenyl diglycidyl ether)
Air transport (ICAO-TI / IATA-DGR):	Environmentally hazardous substance, liquid, n.o.s. (4,4'-methylene diphenyl diglycidyl ether)

14.3. **Transport hazard class(es)**

9

14.4. **Packing group**

III

14.5. **Environmental hazards**

Land transport (ADR/RID) DANGEROUS FOR THE ENVIRONMENT

Marine pollutant	p / 4,4'-methylene diphenyl diglycidyl ether

14.6. **Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.
Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code	-
in packages <= 5 litres	KEIN GUT DER KLASSE 9

Sea transport (IMDG)

EmS-No.	F-A, S-F
in packages <= 5 litres	NOT RESTRICTED 2.10.2.7

Air transport (ICAO-TI / IATA-DGR)

in packages <= 5 litres	NOT RESTRICTED

14.7. **Maritime transport in bulk according to IMO instruments**

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. **Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU legislation

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]
VOC-value (in g/L): 0

National regulations

Restrictions of occupation
Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.

Switzerland: Maternity Protection Ordinance (SR 822.111.52): Pregnant women and nursing mothers may only come into contact with or be exposed to this preparation during their work if it has been established on the basis of a risk assessment by a specialist that, in the context of the activities and the protective measures taken, exposure will not result in harm to the mother or child.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Switzerland: Youth Labour Protection Ordinance (ArGV 5; SR 822.115): Young people up to the age of 18 may only come into contact with or be exposed to this preparation during their work if the Federal Office for Professional Education and Technology (OPET) or the State Secretariat for Economic Affairs (SECO) has authorised an exception.

For professional use only. Product is not intended for consumer use.

Substance/product listed in the following inventories:
AICS listed
DSL listed
EHS no information
IECSC listed
KECI listed
MITI listed
NZLoC no information
PICCS listed
TCSI no information
TSCA listet

15.2. **Chemical Safety Assessment**
For the following substances of this mixture a chemical safety assessment has been carried out:

EC No.	Designation	REACH No.

CAS No.		
216-823-5 1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane	01-2119456619-26
240-260-4 16096-31-4	1,6-hexanediol diglycidyl ether	01-2119463471-41
201-283-5 80-48-8	Methyl toluene-4-sulfonate	01-2120211468-59

SECTION 16: Other information

Full text of classification in section 3:

Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Skin Irrit. 2	Skin corrosion/irritation	Calculation method.
Eye Irrit. 2	Serious eye damage/eye irritation	Calculation method.
Skin Sens. 1	Respiratory or skin sensitisation	Calculation method.
Aquatic Chronic 2	Hazardous to the aquatic environment	Calculation method.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Abbreviations and acronyms

n.a. = not applicable
n.b. = not determined

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and

EU regulations.Without written approval, the product must not be used for purposes different from those mentioned in section 1.It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations.The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.